

Utility Patent Application

CONFIDENTIAL INFORMATION

5 Patent Application based on: Docket No. 03-1328

Inventor: Edwin Shinault

10 Attorneys: John D. Gugliotta, P.E., Esq.
Olen L. York, III, Esq.

TELESCOPICALLY ADJUSTABLE SUPPORT BRACE

RELATED APPLICATIONS

15 The present invention was first described in Disclosure Document
Registration 529,688 filed on April 21, 2003 under 35 U.S.C. §122, 37 C.F.R.
§1.14 and MPEP § 1706. There are no previously filed, nor currently any co-
pending applications, anywhere in the world.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates generally to an adjustable brace, and more particularly, to a telescopically adjustable support brace for maintaining a fixed distance or length between two objects.

2. Description of the Related Art

Poured concrete walls are a common method for building and/or structure construction. They are relatively easy to build, cost-effective and very long lasting. However, they do require some work especially during the form building process to ensure consistent wall thickness and quality of the final product. Most often workers cut 2x4's to use as bracing to hold the form walls apart. However, this procedure has several disadvantages. First, the process is very labor intensive and takes a great deal of time. Second, the wood braces must be pulled out right before the concrete level reaches it, which is difficult to do, considering the rigid nature of the wood. Finally, while some wood braces can be reused for a few times, many of the braces must be discarded after just one use which wastes natural resources and increases landfill levels. Accordingly, there is a need for a means by which concrete forms can be held at a constant and consistent dimension without the disadvantages as listed above.

A search of the prior art did not disclose any patents that read directly on the claims of the instant invention; however, the following references were considered related:

U.S. Patent No. **4,052,031**, issued in the name of *Melfi*, discloses an adjustable concrete form apparatus comprising a pair of spaced form sections properly spaced by spreader sleeves and adjustment means;

U.S. Patent No. **4,202,145**, issued in the name of *Coulter et al.*, discloses a

cast-in-place concrete slab pouring form comprising exterior wall sections containing a series of vertically aligned slots arranged in parallel horizontal rows that can be telescoped into overlapping relation and locked into a free standing position;

U.S. Patent No. **4,949,935**, issued in the name of *Lee*, discloses an apparatus for positioning and supporting an inner mold panel of a form comprising a plurality of supporting members on which the inner steel form mold panels are placed and a plurality of jack devices;

U.S. Patent No. **5,085,398**, issued in the name of *Holcomb et al.*, discloses an adjustable form brace for supporting elevated concrete form floors between support beams comprising two legs connected together at their top by a cradle assembly so that the legs can in a scissors manner;

U.S. Patent No. **5,219,473**, issued in the name of *Sandwith*, discloses an adjustable concrete formwork system comprising at least two spatially oriented upper sleeves with an upper web located on one side of the sleeves, and at least two spatially oriented lower sleeves, and at least two members telescopically connecting upper and lower sleeves therebetween;

U.S. Patent No. **5,393,033**, issued in the name of *Wilson*, discloses an adjustable side form concrete mold for varying the height of a side form on a casting bed to any desired height;

U.S. Patent No. **6,394,410**, issued in the name of *Thompson*, discloses an adjustable reinforcement insertion guide for a slip form concrete barrier mold

comprising a vertically disposed slide gate, a vertically disposed reinforcement screen guide depending from the slide gate; and

U.S. Patent No. **6,519,906**, issued in the name of *Yost et al.*, discloses corner assemblies for concrete form panels, each assembly comprising a dihedral bend, wherein the members are spaced apart by a selected distance and a removable bridge is disposed between the pair of rigid members.

Consequently, there exists a continuous need for new ideas and enhancements for existing products in the concrete forming industry.

SUMMARY OF THE INVENTION

It is therefore an object of the present invention to provide a telescopically adjustable support brace.

It is a feature of the present invention to provide a telescopically adjustable support brace having a pair of crossbars cooperatively and pivotally coupled so that the crossbars are pivotal about one another when required.

It is another feature of the present invention to provide a brace having telescopically adjustable arms for expanding or contracting the length of the brace.

It is another feature of the present invention to provide a brace having pins or cotter-less hitch pins inserted through apertures formed on the arms and crossbars, the pins securing the arms and crossbars at fixed lengths.

It is another feature of the present invention to provide a brace having cleats distally affixed at the ends of the arms.

It is another feature of the present invention to provide a brace having cleats that are threadably adjustable between minor lengths for fine adjustment.

5 It is another feature of the present invention to provide a brace having a lock, the lock having an elongated body with a head terminus and a tail terminus, the tail terminus affixed to a crossbar, and with a downward projection at the head terminus of the body for insertion and impingement within a cavity formed in the opposite crossbar.

10 It is another feature of the present invention to provide a brace having a guard encompassing the lock, wherein the guard prevents hyper extension of the lock and damage and/or failure of the lock.

 It is another feature of the present invention to provide a retention member along an anterior surface of the lock, the retention member comprising
15 an orifice for receiving a wire, wherein a user may collapse, pivot or fold the crossbars upward by urging the wire upward, thereby allowing the crossbars to pivot and permit extraction of the brace from a considerable distance or height.

 Briefly described according to one embodiment of the present invention, a telescopically adjustable support brace is used to hold concrete form work at the
20 proper dimension during pouring operations. The brace utilizes two sets of crossbars and adjustable arms, which slide inside of one another and are locked

into place using a pin in a series of equally spaced apertures. At the distal ends of each arm, a cleat is provided which is serrated in nature and which digs into the form wall to prevent slippage. The cleats are connected to the arms by a threaded rod, which allows for an infinite range of fine adjustments by simply rotating the cleats. The crossbars are connected by a pivot bolt or hinge, which is held in place by a spring. When the bolt or hinge is locked in place, the invention forms a rigid assembly, which holds the concrete form walls apart. The hinge or bolt is released by pulling up on it with the aid of a wire tie, which is threaded through a retention member coupled to the clip. When it is released, the brace pivots about the crossbars, which allows it to be easily removed through the top of the form, and the concrete pour can continue. The use of the brace allows for the pouring of concrete walls in not only a quicker manner when compared to conventional methods, but in a more accurate manner as well.

It is an advantage of the present invention to provide a brace that is easily disassembled after use, thereby permitting a user to remove excess concrete from the brace and prevent damage and/or failure to the brace for subsequent use.

It is a further advantage of the present invention to provide a brace that is easily extracted from the pouring forms as the level of concrete rises therein.

BRIEF DESCRIPTION OF THE DRAWINGS

The advantages and features of the present invention will become better understood with reference to the following more detailed description and claims taken in conjunction with the accompanying drawings, in which like elements are identified with like symbols, and in which:

FIG. 1 is an exploded perspective view of the telescopically adjustable support brace insertable between wall forms for manufacturing concrete walls;

FIG. 2 is an exploded perspective view of the brace insertable between reinforcement bar (as shown);

FIG. 3 is a perspective view of the brace;

FIG. 4 is another perspective view of the brace;

FIG. 5 is a partial perspective view of the brace and the pivotal articulation that the brace performs about the pivoting hinge or bolt;

FIG. 6 is a front perspective of the brace illustrating the clip with retention member and wire inserted therethrough;

FIG. 7 is a front perspective of the brace illustrating the lock that further secures the clip to the crossbar;

FIG. 8 is a perspective view of the brace also illustrating the lock in position; and

FIG. 9 is a top view of the clip with the clock and cotter-less hitch pins for securing the arms and crossbars at fixed lengths.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The best mode for carrying out the invention is presented in terms of its preferred embodiment, herein depicted within Figures 1 through 9.

1. Detailed Description of the Figures

5 Referring now to FIG. 1 through FIG. 9, a telescopically adjustable support brace **10** (hereinafter "brace") is shown in accordance with a preferred embodiment of the present invention. The brace **10** is envisioned for use in maintaining a specified linear distance or width between two objects, especially two objects that may tilt beyond a vertical or substantially vertical position. By way of example only, and not a limitation on the scope of the invention as claimed, in **FIG. 1**, the brace **10** is shown in supporting two wall forms **100** to prevent tilting of the wall forms **100** toward one another. In **FIG. 2**, the brace **10** is shown in supporting two upstanding reinforcement bars **102** (or re-bar as it is known in the trade). The brace **10** comprises a linearly elongated crossbar (generally denoted as **12**) terminating at opposing ends **34** and **36**. The brace 10 also includes a pair of adjustable arms **38** and **40**, wherein each one of the pair of arms **38** and **40** is inserted at an end **34** and **36** of crossbar **12** and are telescopically adjustable therein. The brace **10** further includes a pair of cleats **42** and **44**, wherein each one of the cleats **42** and **44** is distally affixed to an arm **38** and **40**, respectively.

The crossbar **12** comprises a first crossbar **14** and a second crossbar **16** pivotally coupled about pivot means **18**. Pivot means **18** is envisioned as any mechanism that permits the first crossbar **14** and second crossbar **16** to pivot as required, the pivoting about pivot means **18** resulting in crossbar ends **34** and **36** assuming a lower profile position relative to pivot means **18**. Included among the envisioned mechanisms are hinges of various types, pivot bolt **20**, or a lock **22**, or a combination of the recited mechanisms.

The clip **22** comprises an elongated body having a head terminus and a tail terminus, wherein the tail terminus affixed to the first crossbar **14** or the second crossbar **16**. At an opposite head terminus of the lock **22**, a projection **24** extends downward therefrom, the projection **24** inserted into and impinged within a cavity **28** formed in the opposite crossbar **14** or **16**. The projection **24** and cavity **28** are coupled (when desired) in an impinging manner to maintain the horizontal integrity of the brace **10** during use. For illustration and example only, the lock **22** is affixed to second crossbar **16** and the cavity **28** is formed in the first crossbar **14**. Along an upper or anterior surface of the lock **22**, a retention member **30** is provided for receiving wire (denoted as **W** in the figures), cable, rope, string, twine or other similar items. Wire **W**, for example, is passed through the retention member **30**. The wire permits a user to manually pivot first crossbar **14** and second crossbar **16**, thereby releasing the brace **10** from between the objects the brace **10** supports. The incorporation of retention

member **30** and wire is advantageous in use with concrete forms and reinforcement bar, wherein the user can safely and conveniently observe from a distance and then extract the brace **10** by tugging on the wire, releasing the projection **24** from the cavity **28**, resulting in pivotal collapsing of first crossbar **14** and second crossbar **16**, thus releasing the brace **10** from between the objects. A lock retainer or guard **32** may be included to further secure the lock **22** to the cavity **28**. The guard **32** is envisioned as being either permanently or semi-permanently affixed to crossbar **14** or **16** to which the lock **22** is affixed at the tail terminus and encompassing the lock **22**. As shown, the guard **32** is affixed about one or both of its ends to the crossbar **16**. To release the lock **22** from cavity **28**, the guard **32** is positioned so that a space or interstice **S** exists between the lock **22** and guard **32**. The space/interstice **S** allows the lock **22** to urge upward when influenced by tugging on wire **W**. Upward urging of lock **22** releases projection **24** from cavity **28**, and thus releases crossbars **14** and **16** from one another. The guard **32** further prevents hyper extension of lock **22** and potential damage and/or failure of lock **22** in subsequent uses.

The first crossbar **14** and second crossbar **16** each comprise a plurality of apertures **46** that traverse the respective diameters of crossbars **14** and **16**. The apertures **46** are provided to cooperatively correspond with a plurality of apertures **46** formed in arms **38** and **40**. Alignment of the apertures **46** of the crossbars **14** and **16** with the apertures **46** of the arms **38** and **40** permits

insertion of pins **48** to securely position arms **38** and **40** within the crossbars **14** and **16** at a fixed length. In an alternate embodiment, cotterless hitch pins **50** are used, wherein a user would remove the hitch pin **50**, releasing the impingement on arm **38** or **40**, thereby permitting telescopic adjustment of the arms **38** and **40**. In one envisioned embodiment, the apertures **46** are provided at approximately one inch intervals, although other linear intervals are envisioned. The intervals are envisioned as providing the greatest flexibility in allowing specific linear distances between objects, and in combination with the fine adjustment provided by the cleats **42** and **44** and shafts **56** and **58**, respectively, a user will be able to achieve precise linear lengths of the brace **10** for supporting objects upstanding at specific linear distances.

The cleats **42** and **44** each comprise a plurality of recesses **52** for receiving a rod/bar **102**. The recesses **52** shown in the figures are formed from a V-shape, but other shapes and configurations are envisioned. The configuration illustrated by the figures illustrate the recesses **52** forming points, or crimps **54** provided for situations in which objects may be wider or larger than the recesses **52** in cleats **42** or **44**. The points **54** act to press against the objects (such as concrete wall forms **100**), bracing the objects and maintaining a fixed length or distance between the objects. The cleats **42** and **44** are envisioned as providing resistance to inward collapse of a wall form **100** (in one example) and for preventing lateral and longitudinal displacement due to shifting

that may occur during use. The cleats **42** and **44** are affixed to threaded shafts **56** and **58** depending from the arms **38** and **40**. The threads **60** are provided to allow for fine adjustment of the brace **10** once an appropriate length is established. By rotating the cleats **42** or **44** about the respective threads (the cleats having corresponding complimentary threads), a user can perform minor adjustments in length about the brace **10**. The cleats **42** and **44** may also be affixed or coupled with shafts **56** and **58** via a coupling nut (not shown) therebetween, wherein the nut is permanently affixed to the cleats **42** and/or **44** and then receives the threads **60** from shafts **56** and/or **58**. In one envisioned embodiment, shafts **56** and **58** are coupled with arms **38** and **40** via a permanent attachment, which may be accomplished by welding or another similar means. In another envisioned embodiment, shafts **56** and **58** are coupled with arms **38** and **40** by alignment of apertures **46** formed in arms **38** and **40** with apertures **46** formed in shafts **56** and **58** and impinged by pins **48** or **50**.

Because the invention is particularly envisioned as advantageous in use with wall forms **100** (or reinforcement bar used to reinforce poured concrete), the brace **10** is envisioned as being commercially available in dimensions particularly suited for such use. As such, three sizes are envisioned: a minimum length (between twelve inches and eighteen inches), an intermediate length (between eighteen inches and thirty inches) and an maximum length (between thirty inches and fifty-four inches). These three sizes are intended to account for a majority of

the fixed lengths between wall forms **100** (or reinforcement bar **102**) used on construction sites, spanning the desired thickness of the subsequently completed concrete wall.

It is envisioned that the brace **10** is constructed from a durable and sturdy material, such as steel or other suitable metals, although hardened plastics are also envisioned. It is recommended that any excess concrete or cement, or other foreign material, that accumulates on the brace **10** is removed as quickly as practicable to prevent hardening of the material and damaging, limiting the use or shortening the useful life of the brace **10**, especially concerning the apertures **46** being plugged by material, or interference of the telescopic nature of the arms **38** and **40**.

2. Operation of the Preferred Embodiment

To use the present invention, in accordance with a preferred embodiment of the present invention, the brace **10** is adjusted to an approximate length spanning the linear distance or width between two objects, such as the wall forms **100** or reinforcement bars/rods **102** shown in the figures. Adjustment is accomplished by removing the pins **48** or pins **50** so as to release the arms **38** and **40** from impingement with the crossbars **14** and **16**. The arms **38** and **40** are then telescopically adjusted. Upon appropriate adjustment, the pins **48** or **50** are returned to impinge the arms **38** and **40** and crossbars **14** and **16**. The

cleats **42** and **44** are then rotated about the threads **60** to finely adjust the length.

A wire, cable, rope, twine or string is threaded through a retention member **30** at the top of lock **22**. When the brace **10** is no longer needed at the position it is

set, a user can tug on the wire or cable, which pulls the retention member **30**

upward, releasing the lock **22** from the cavity **28**, and thereby allowing the

crossbars **14** and **16** to pivot upward and allow for the brace **10** to be removed

from between the objects, the objects envisioned include wall forms,

reinforcement bar, upstanding poles, rods, dowels, lumber, or other similar items.

The foregoing descriptions of specific embodiments of the present invention have been presented for purposes of illustration and description. They are not intended to be exhaustive or to limit the invention to the precise forms disclosed, and obviously many modifications and variations are possible in light of the above teaching. The embodiments were chosen and described in order to best explain the principles of the invention and its practical application, to thereby enable others skilled in the art to best utilize the invention and various embodiments with various modifications as are suited to the particular use contemplated. It is intended that the scope of the invention be defined by the Claims appended hereto and their equivalents. Therefore, the scope of the invention is to be limited only by the following claims.